

Minerals Management Service, Interior

§250.1741

(a) A summary of the removal operation including the date it was completed;

(b) A description of any mitigation measures you took; and

(c) A statement signed by your authorized representative that certifies that the types and amount of explosives you used in removing the platform or other facility were consistent with those set forth in the approved removal application.

§250.1730 When might MMS approve partial structure removal or toppling in place?

The Regional Supervisor may grant a departure from the requirement to remove a platform or other facility by approving partial structure removal or toppling in place for conversion to an artificial reef or other use if you meet the following conditions:

(a) The structure becomes part of a State artificial reef program, and the responsible State agency acquires a permit from the U.S. Army Corps of Engineers and accepts title and liability for the structure; and

(b) You satisfy any U.S. Coast Guard (USCG) navigational requirements for the structure.

SITE CLEARANCE FOR WELLS, PLATFORMS, AND OTHER FACILITIES

§250.1740 How must I verify that the site of a permanently plugged well, removed platform, or other removed facility is clear of obstructions?

Within 60 days after you permanently plug a well or remove a platform or

other facility, you must verify that the site is clear of obstructions by using one of the following methods:

(a) For a well site, you must either:

(1) Drag a trawl over the site;

(2) Scan across the location using sonar equipment;

(3) Inspect the site using a diver;

(4) Videotape the site using a camera on a remotely operated vehicle (ROV); or

(5) Use another method approved by the District Supervisor if the particular site conditions warrant.

(b) For a platform or other facility site in water depths less than 300 feet, you must drag a trawl over the site.

(c) For a platform or other facility site in water depths 300 feet or more, you must either:

(1) Drag a trawl over the site;

(2) Scan across the site using sonar equipment; or

(3) Use another method approved by the Regional Supervisor if the particular site conditions warrant.

[67 FR 35406, May 17, 2002; 67 FR 66049, Oct. 30, 2002]

§250.1741 If I drag a trawl across a site, what requirements must I meet?

If you drag a trawl across the site in accordance with §250.1740, you must meet all of the requirements of this section.

(a) You must drag the trawl in a grid-like pattern as shown in the following table:

For a—	You must drag the trawl across a—
(1) Well site	300-foot-radius circle centered on the well location.
(2) Subsea well site	600-foot-radius circle centered on the well location.
(3) Platform site	1,320-foot-radius circle centered on the location of the platform.
(4) Single-well caisson, well protector jacket, template, or manifold.	600-foot-radius circle centered on the structure location.

(b) You must trawl 100 percent of the limits described in paragraph (a) of this section in two directions.

(c) You must mark the area to be cleared as a hazard to navigation according to USCG requirements until you complete the site clearance procedures.

(d) You must use a trawling vessel equipped with a calibrated navigational positioning system capable of providing position accuracy of ± 30 feet.

(e) You must use a trawling net that is representative of those used in the commercial fishing industry (one that